

Connection technology

M12 connection technology

Cordsets, pre-assembled

With connector, 5 pin

Working temp. -30°C ... +80°C [-22°F ... +176°F]


Order no.

Female connector with coupling nut + single-ended
A coded, straight

Cable: PUR, 4 x 0.34 mm² [AWG22]
 Housing: metal / plastic, IP67



Bus-in



suitable for our series:

IS60, IN88
 SR160, SR250H

DeviceNet

Terminal assignment

| | | | | | |
|----------------------|------|----|----|----|----|
| Pin female contacts: | 1 | 2 | 3 | 4 | 5 |
| Core color: | ± 3) | RD | BK | WH | BU |

cable length ¹⁾

| | |
|--------------------------|---------------|
| standard cable length | 2 m [6.56'] |
| (available from 1 piece) | 5 m [16.40'] |
| | 10 m [32.81'] |
| | 15 m [49.21'] |

05.00.6021.2211.002M
05.00.6021.2211.005M
05.00.6021.2211.010M
05.00.6021.2211.015M

other cable lengths
 (minimum order quantity 4 pieces)

05.00.6021.2211.0xxM
 xx = length in meters:
 1, 3, 8, 12, 20, 25, 30

1) Other cable lengths on request.
 2) Shield on housing.
 3) Shield with pin 1.